

CUW29 FLOOR STANDING SERIES



CUW291

FEATURES

PUSH BUTTON BUBBLER

Adjustable stream height is automatic with variation pressure up to 100 P.S.I. Heavy chrome plating and protective guard satisfy all sanitary safety requirements.

STAINLESS STEEL TOP & COOLING TANK

Polished to resist rust, corrosion and stains. Anti-splash ridge and integral drain direct and dispose of water.

Offers maximum cooling efficiency and reduces starts of the compressor.

ARC DESIGN

Front panel is a classic arc design.

INSULATION JACKET & ADJUSTABLE THERMOSTAT

Expanded polystyrene foam insulation maintains chilled water temperature. Tamper-proof remote sensing bulb located in cooling tank provides accurate control of chilled water temperature.

PRODUCT SPECIFICATIONS

MODEL	CUW293	CUW291
TYPE	Floor Standing Cold only	Floor Standing Hot/Cold
DIMENSIONS	430mm (W) 300mm (D) 1240mm (H)	430mm (W) 300mm (D) 1240mm (H)
WEIGHT	29kg	32kg
TANK CAPACITY	Cold—10L/hr (3L) Hot—N.A	Cold—10L/hr (3L) Hot—8L/hr (5L)
POWER	Cold—200W Hot—N.A	Cold—200W Hot—750W
REGULATED POWER	AC 220-240V, 120V 50-60Hz	AC 220-240V, 120V 50-60Hz
REFRIGERANT	R134A	R134A

Filtration System

- ∅ **SPACE SAVER FILTER**
- ∅ **IN-LINE FILTER**

* Filtration system and upgrades are available upon request.

