

CUW600 FLOOR STANDING SERIES



FEATURES

PUSH BUTTON BUBBLER

Adjustable stream height is automatic with variation pressure up to 100 P.S.I. Heavy chrome plating and protective guard satisfy all sanitary safety requirements.

STAINLESS STEEL TOP & COOLING TANK

Polished to resist rust, corrosion and stains. Anti-splash ridge and integral drain direct and dispose of water.

Offers maximum cooling efficiency and reduces starts of the compressor.

COPPER COOLING COILS

Are bonded around the outside of the stainless steel cooling tank. Double-wall separation is provided between refrigerant and drinking water.

INSULATION JACKET & ADJUSTABLE THERMOSTAT

Expanded polystyrene foam insulation maintains chilled water temperature. Tamper-proof remote sensing bulb located in cooling tank provides accurate control of chilled water temperature.

PRODUCT SPECIFICATIONS

MODEL	CUW600	CUW600A	CUW300A**
TYPE	Floor Standing Cold only	Floor Standing Hot/Cold	Floor Standing Hot/Warm
DIMENSIONS	380mm (W) 330mm (D) 1015mm (H)	380mm (W) 330mm (D) 1015mm (H)	380mm (W) 330mm (D) 1015mm (H)
WEIGHT	37kg	41kg	35kg
TANK CAPACITY 3.3L	Cold—11L/hr Hot—N.A	Cold—11L/hr Hot—8L/hr	Warm —11/hr Hot—8L/hr
POWER	Cold—215W Hot—N.A	Cold—215W Hot—750W	Hot—750W
REGULATED POWER	AC 220-240V, 120V 50-60Hz	AC 220-240V, 120V 50-60Hz	AC 220-240V, 120V 50-60Hz

Filtration System

- ∅ SPACE SAVER FILTER
- ∅ IN-LINE FILTER

* Filtration system and upgrades are available upon request.

**CUW300A MOQ: 40 units

